# SAFETY DATA SHEET



### 1. Identification

**Product identifier Harvey Seal** 

Other means of identification

**Product code** 3703E

**Synonyms** Part Numbers: 025020, 025050, 025080

Recommended use Pipe Joint Compound for Threaded Metal Pipes

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

William H. Harvey Company **Company Name Address** 4334 South 67th Street

Omaha, NE 68117

402-331-115 **Telephone** E-mail info@oatev.com

**Transport Emergency** Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

**Emergency First Aid** 1-877-740-5015 **Contact person MSDS** Coordinator

# 2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards OSHA** defined hazards Not classified.

Label elements

**Hazard symbol** None. None. Signal word

**Hazard statement** The mixture does not meet the criteria for classification.

**Precautionary statement** 

Observe good industrial hygiene practices. Prevention

Wash hands after handling. Response

Storage Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. **Disposal** 

Hazard(s) not otherwise

classified (HNOC)

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

SDS US

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%	
Calcium carbonate	1317-65-3	60-70	
Oxidized Soy Bean Oil	68152-81-8	10-20	
2-Butoxyethanol	111-76-2	5-10	
Silicon Dioxide	112926-00-8	1-5	
Crystalline silica (Quartz)	14808-60-7	< 1.5	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Harvey Seal 1/8

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Treat symptomatically.

Indication of immediate medical attention and special treatment needed

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting Move containers from fire area if you can do so without risk. equipment/instructions

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

**Environmental precautions** 

7. Handling and storage

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.	1000)		
Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.

Harvey Seal SDS US

### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Silicon Dioxide (CAS 112926-00-8)	TWA	0.8 mg/m3	
		20 mppcf	

#### **US. ACGIH Threshold Limit Values**

Components	Туре	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

#### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
,		5 ppm	
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Silicon Dioxide (CAS 112926-00-8)	TWA	6 mg/m3	

### **Biological limit values**

# **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time	
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

### **Exposure guidelines**

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies** 

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

**US - Tennessee OELs: Skin designation** 

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

**US. NIOSH: Pocket Guide to Chemical Hazards** 

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

**Respiratory protection**Use a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

Harvey Seal
924490 Version #: 01 Revision date: - Issue date: 05-February-2015

.

**General hygiene** considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.

Liquid. Liquid paste. **Form** 

Color Yellow. Petroleum. Odor **Odor threshold** Not available. Not available. рH Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

153.0 °F (67.2 °C) Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available.

> 1 Vapor density

Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. Not available. **Decomposition temperature** 30000 cP **Viscosity** 

Other information

VOC (Weight %) 119 g/l

## 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Acids. Strong oxidizing agents. Fluorine. Incompatible materials

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

### 11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and Skin contact

prolonged. These effects have not been observed in humans.

SDS US Harvey Seal 924490 4/8 Issue date: 05-February-2015 Version #: 01 Revision date: -

Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

### Information on toxicological effects

**Acute toxicity** 

Components **Species** Test Results

Silicon Dioxide (CAS 112926-00-8)

Acute Oral

LD50 Rat > 22500 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica Carcinogenicity

inhaled from occupational sources can cause lung cancer in humans. However in making the

overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to

humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

### IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

Crystalline silica (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

Silicon Dioxide (CAS 112926-00-8) 3 Not classifiable as to carcinogenicity to humans.

**NTP Report on Carcinogens** 

Crystalline silica (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** 

Not an aspiration hazard.

**Chronic effects** May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

5/8

prolonged. These effects have not been observed in humans.

Prolonged exposure may cause chronic effects.

**Further information** This product has no known adverse effect on human health.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

SDS US Harvey Seal

924490 Revision date: -Version #: 01 Issue date: 05-February-2015

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol (CAS 111-76-2)

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

0.83

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

**General information** DOT: Not regulated as dangerous goods except when shipped in bulk. This material is not

regulated if in a container of 119 gallon (450 L) capacity or less.

15. Regulatory information

**US** federal regulations All components are on the U.S. EPA TSCA Inventory List.

Not established.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2)

LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No **Hazard categories** 

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

**Chemical name** CAS number % by wt. 2-Butoxyethanol 111-76-2 5-10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Harvey Seal SDS US

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

### **US** state regulations

### **US. Massachusetts RTK - Substance List**

2-Butoxyethanol (CAS 111-76-2) Calcium carbonate (CAS 1317-65-3) Crystalline silica (Quartz) (CAS 14808-60-7) Silicon Dioxide (CAS 112926-00-8)

### US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2) Calcium carbonate (CAS 1317-65-3) Crystalline silica (Quartz) (CAS 14808-60-7) Silicon Dioxide (CAS 112926-00-8)

### US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2) Calcium carbonate (CAS 1317-65-3) Crystalline silica (Quartz) (CAS 14808-60-7)

#### **US. Rhode Island RTK**

2-Butoxyethanol (CAS 111-76-2)

### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Crystalline silica (Quartz) (CAS 14808-60-7)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

# 16. Other information, including date of preparation or last revision

**Issue date** 05-February-2015

Revision date Version # 01
HMIS® ratings Health: 0

United States & Puerto Rico

Flammability: 2 Physical hazard: 0

NFPA ratings

0 0

Harvey Seal SDS US

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### Disclaimer

William H. Harvey Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Harvey Seal SDS US